FARMTECH OF PROGRESS

www.fop.hu

FOP - KOMPAKTOR

- Working width: 3 - 8 m
- A machine for pre-set soil preparation in one pass
- The costs of soil cultivation are reduced many times over and the loss of moisture is reduced

FOP - VIBROCULT

- Working width: 2,1 - 12 m
- Optimum seed bed preparation for large farms in optimized sizes
- Economical use due to the low traction requirement

FOP - ECOHARROW

- Working width: 3 - 7 m
- For clod crushing, seedbed preparation, furrow closing
- Required HP: 80 - 170 HP

FOP - GERMINATOR

- Working width: 3 - 9 m
- Precise sowing preparation ensures a higher yield
- Ground tracking mechanism

FOP - INJECTMASTER

- Working width: 3 - 10,5 m
- It delivers nutrients directly to the plant's root system
- The spikes do not damage the plant's root system

FOP - DOZATOR

- Liter capacity 660 - 1100 lit
- Two-stage filtering with 50 fine MESH filters
- Optional ISOBUS control function

FOP - AGROBEAR

- Working width: 2.5 - 3 m
- An excellent tool for reducing tillage
- Available with several types of rollers

FOP - ECODISC

- Working width: 3 - 6 m
- Creates ideal conditions for seed germination
- Optimal for shallow tillage

FOP - V ECODISC

- Working width: 2.8 - 3.2 m
- Stubble stripping, fertilizer-chemical mixing, seedbed preparation, plowing replacement, seedbed preparation

FOP - AGROCUT

- Working width: 3 - 8 m
- The machine was developed for shredding crop residues
- Aviable mounted or trailed version

FOP - AGROTILL

- Low traction requirement
- Wear plates combined with a cutting edge
- Loosening the plow sole and mixing stem residues into the soil

FOP - VULCAN

- Available with 2, 3 or 4 plow heads
- Easy adjustability, simple handling
- Reversible or conventional design

FOP - RowCult Classic

- Traditional interrow cultivators
- Option with fertilizer spreader
- Easy to set up, simple to use

FOP - RowCult S tine

- Interrow cultivators with S tines
- Delivers liquid fertilizer directly to the place of use
- Hydraulic or shift driving

FOP - TrakUp

- Lifting the tractor using its own hydraulics
- Simultaneous lifting of wheels on the same axle
- Timesaving, risk residue

FOP - Jumbo

- Big help when moving loads on farms and in fields
- Load capacity: 1 t
- Maximum lift height: 3720 mm

FOP - FOP Original Parts

- Welding, cutting, heat treatment, painting section in local
- Precision machine and steel forming
- Compatible with leading brands

FOP - Dumbo

- Available in 450, 750 and 1000 kg version
- Reinforced structure, with towing eye
- Optional practical front toolbox

Address:

FOP Ltd.
Dolmány u. 18-20
1131 Budapest
HUNGARY

FARMTECH OF PROGRESS

Contact:

E-mail: office@fop.hu
Tel: +36 70 942 9860
Web: www.fop.hu